SPECIFICATION SHEET

Belting Range

Issue 2 – November 2026

The KBR conveyor belting range: belts we cut and join to your size, each with its own product data sheet. Belts marked 'on request' are supplied to order – please ask for a quote.

PVC CONVEYOR BELTS					
Reference	**Belt**	**Thickness**	**Min pulley**	**Temp °C**	**Food (FDA)**
KBR-PVC20-BK	Black PVC 2.0mm	2.00mm	40mm	-10 / +70	–
KBR-PVC20-GN	Green PVC 2.0mm	2.00mm	40mm	-10 / +70	–
KBR-PVC20-BL	Blue PVC 2.0mm	2.0mm	40mm	-10 / +70	–
KBR-PVC20-WH	White PVC 2.0mm	2.0mm	40mm	-10 / +70	–
KBR-PVC25-LG	Black PVC Longitudinal Ribbed 2.5mm	2.50mm	40mm	-10 / +100	–

PVC DIAMOND BACK BELTS					
Reference	**Belt**	**Thickness**	**Min pulley**	**Temp °C**	**Food (FDA)**
KBR-PVC32-WH	White PVC Diamond Back 3.2mm	3.20mm	50mm	-10 / +70	Yes
KBR-PVC32-BL	Blue PVC Diamond Back 3.2mm	3.20mm	60mm	-10 / +70	Yes

GRIP TOP BELTS					
Reference	**Belt**	**Thickness**	**Min pulley**	**Temp °C**	**Food (FDA)**
KBR-GRIP52-GN	Green PVC Grip Top 5.2mm	5.20mm	60mm	-10 / +70	–
KBR-GRIP52-BK	Black PVC Grip Top 5.2mm	5.20mm	60mm	-10 / +70	–
KBR-GRIP52-BL	Blue PVC Wavy Grip Top 5.2mm	5.20mm	60mm	-10 / +70	Yes
KBR-STK-BL	Blue High-Grip Sticky Top (on request)	~3.0mm	60mm	-10 / +60	–
KBR-GRIP-LP-GY	Grey Low Profile Grip Top (on request)	~3.0mm	50mm	-10 / +70	–

PU FOOD GRADE BELTS					
Reference	**Belt**	**Thickness**	**Min pulley**	**Temp °C**	**Food (FDA)**
KBR-PU13-BL	Blue PU 1.3mm	1.3mm	20mm	-10 / +100	Yes
KBR-PU13-WH	White PU 1.3mm	1.3mm	20mm	-10 / +100	Yes
KBR-PU22-WH	White PU Extra Rigid 2.2mm	2.2mm	80mm	-10 / +80	Yes
KBR-PU22-BL	Blue PU Extra Rigid 2.2mm	2.2mm	80mm	-10 / +80	Yes

PU OIL RESISTANT BELTS					
Reference	**Belt**	**Thickness**	**Min pulley**	**Temp °C**	**Food (FDA)**
KBR-PU15-BK-OR	Black PU Oil Resistant 1.5mm	1.5mm	30mm	-10 / +80	–
KBR-PU15-GN-OR	Green PU Oil Resistant 1.5mm	1.5mm	30mm	-10 / +80	–
KBR-PU18-OR	PU Oil Resistant 1.8mm (on request)	1.8mm	40mm	-10 / +80	–
KBR-PU25-BK-OR	Black PU Oil Resistant 2.5mm	2.5mm	60mm	-10 / +80	–

HEAVY DUTY 3-PLY BELTS					
Reference	**Belt**	**Thickness**	**Min pulley**	**Temp °C**	**Food (FDA)**
KBR-HD36-OR	Heavy Duty Oil Resistant 3.6mm	3.6mm	80mm	-10 / +80	–
KBR-HD50-OR	Heavy Duty Oil Resistant 5.0mm	5.0mm	100mm	-10 / +80	–
KBR-HD-BWL	Heavy Duty Bowling Alley	~4.0mm	80mm	-10 / +70	–

FELT BELTS					
Reference	**Belt**	**Thickness**	**Min pulley**	**Temp °C**	**Food (FDA)**
KBR-FLT25-WH	White Felt Top 2.5mm	2.5mm	30mm	-10 / +100	–
KBR-FLT60-GY	Grey Felt Top 6.0mm	6.0mm	80mm	-10 / +100	–

NOTES

- Figures are typical values. ~ = approximate; exact figures are confirmed with your quotation.
- All belts can be supplied with tracking guides, flights / cleats or sidewalls – see our technical guides.
- Belts are made to order to your size and are non-returnable. Samples can be ordered online.

01952 583 837 | sales@conveyorsections.co.uk | www.conveyorsections.co.uk

KBR Conveyor Sections, Units B1 & B2, Halesfield 11, Telford, Shropshire, TF7 4PH